



---

Images

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE  
PATENT COOPERATION TREATY (PCT)

(11) WO 98/16889

(13) A1

(21) PCT/JP97/03419

(22) 24 September 1997 (24.09.1997)

(25) Japanese

(26) Japanese

(30) 8/273829

16 October 1996  
(16.10.1996)

JP

(43) 23 April 1998 (23.04.1998)

(51)<sup>6</sup> G06F 17/22

(54) CHARACTER INPUT APPARATUS AND STORAGE MEDIUM IN  
WHICH CHARACTER INPUT PROGRAM IS STORED

(71) SHARP KABUSHIKI KAISHA [JP/JP]; 22-22, Nagaike-cho,  
Abeno-ku, Osaka-shi, Osaka 545 (JP).

(72) NAKAGAWA, Katsuya [JP/JP]; 45-3, Takama-cho, Nara-shi,  
(75) Nara-ken 630 (JP).

(74) YAMAMOTO, Shusaku; Crystal Tower, 15th floor, 2-27, Shiromi  
1-chome, Chuo-ku, Osaka-shi, Osaka 540 (JP).

(81) CN, JP, KR, US

(84) European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT,  
LU, MC, NL, PT, SE)